Serial No.: 10/783,601 Filed: February 20, 2004

Page 2 of 11

In the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- 1. (Original) A portable electronic device, comprising:
- a housing;
- a display integrated with the housing;
- a thumb-operable input device positioned on a side of the housing;
- an indicator on the display operatively associated with the thumb-operable input device, the indicator being positioned on the display to highlight and/or select menu items on the display responsive to input received at the thumb-operable input device.
- 2. (Original) The device of Claim 1 wherein the thumb-operable input device comprises at least one thumb position sensor and wherein the thumb position sensor is configured to detect a position of a thumb on the thumb-operable input device and move the indicator on the display between the menu items responsive to the position of the thumb on the thumb-operable input device.
- 3. (Original) The device of Claim 1 wherein the thumb-operable input device further comprises:
- at least one thumb movement sensor configured to detect movement on the thumboperable input device; and
- a processor operatively associated with the at least one thumb movement sensor, the processor being configured to process the detected movement and move the indicator on the display between the menu items responsive to the processed movement.
- 4. (Original) The device of Claim 3, wherein the thumb movement sensor is further configured to detect movement via fingerprint analysis.
- 5. (Original) The device of Claim 4, wherein the thumb movement sensor is further configured to detect distortion of a fingerprint on the thumb-operable input device and wherein the processor is further configured to process the detected distortion of the

Serial No.: 10/783,601 Filed: February 20, 2004

Page 3 of 11

fingerprint and highlight and/or select menu items on the display responsive to the detected distortion.

6. (Original) The device of Claim 1, wherein the thumb-operable input device comprises:

a slot; and

a bar configured to slide in the slot to position the indicator on the display to highlight and/or select one of a plurality of menu items.

7. (Original) The device of Claim 6, wherein the thumb-operable input device further comprises:

a plurality of notches in the slot, each of the plurality of notches being associated with one of the plurality of menu items, wherein the bar is further configured to move in the slot between the notches to position the indicator on the display to highlight and/or select the associated menu item.

8. (Original) The device of Claim 7 further comprising:

a sensor operatively associated with the bar and configured to detect movement of the bar in the slot; and

a processor operatively associated with the sensor, the processor being configured to process the detected movement of the bar and move the indicator on the display between the menu items responsive to the processed movement.

- 9. (Original) The device of Claim 6 wherein the thumb-operable input device further comprises a spring mechanism, the spring mechanism being configured to reposition the bar at an end of the slot between selections of menu items.
- 10. (Original) The device of Claim 1 wherein the thumb-operable input device comprises at least one of a fingerprint sensor, touchpad or hinged bar, wherein the indicator is configured to move between menu items responsive to upward and/or downward movement on the fingerprint sensor, the touchpad or the hinged bar.

Serial No.: 10/783,601 Filed: February 20, 2004

Page 4 of 11

11. (Original) The device of Claim 1, wherein the thumb-operable input device comprises a touchpad positioned on a side of the housing.

12. (Original) The device of Claim 11 further comprising:

a sensor operatively associated with the touchpad and configured to detect movement on the touchpad; and

a processor operatively associated with the sensor, the processor being configured to process the detected movement on the touchpad and move the indicator on the display between the menu items responsive to the processed movement.

13. (Original) A man-machine interface (MMI) for a portable electronic device, comprising:

a thumb-operable input device; and

an indicator on a display of the portable electronic device, the indicator being operatively associated with the thumb-operable input device and positioned on the display to highlight and/or select menu items on the display responsive to input received at the thumb-operable input device.

- 14. (Original) The MMI of Claim 13 wherein the thumb-operable input device comprises at least one thumb position sensor and wherein the thumb position sensor is configured to detect a position of a thumb on the thumb-operable input device and move the indicator on the display between the menu items responsive to the position of the thumb on the thumb-operable input device.
- 15. (Original) The MMI of Claim 13 wherein the thumb-operable input device further comprises:

at least one thumb movement sensor configured to detect movement on the thumboperable input device; and

a processor operatively associated with the at least one thumb movement sensor, the processor being configured to process the detected movement and move the indicator on the display between the menu items responsive to the processed movement.

Serial No.: 10/783,601 Filed: February 20, 2004

Page 5 of 11

16. (Original) The MMI of Claim 15, wherein the thumb movement sensor is further configured to detect movement via fingerprint analysis.

- 17. (Original) The MMI of Claim 16, wherein the thumb movement sensor is further configured to detect distortion of a fingerprint on the thumb-operable input device and wherein the processor is further configured to process the detected distortion of the fingerprint and highlight and/or select menu items on the display responsive to the detected distortion.
- 18. (Original) The MMI of Claim 14 wherein the thumb-operable input device comprises:

a slot; and

a bar configured to slide in the slot to position the indicator on the display to highlight and/or select one of a plurality of menu items.

19. (Original) The MMI of Claim 18 wherein the thumb-operable input device further comprises:

a plurality of notches in the slot, each of the plurality of notches being associated with one of the plurality of menu items, wherein the bar is configured to move in the slot between the notches to position the indicator on the display highlight and/or select the associated menu item.

- 20. (Original) The MMI of Claim 19 wherein the bar is operatively associated with a sensor that is configured to detect movement of the bar in the slot and wherein the sensor is operatively associated with a processor that is configured to process the detected movement of the bar and move the indicator on the display between the menu items responsive to the processed movement.
- 21. (Original) The MMI of Claim 18 wherein the thumb-operable input device further comprises a spring mechanism, the spring mechanism being configured to reposition the bar at an end of the slot between selections of menu items.

Serial No.: 10/783,601 Filed: February 20, 2004

Page 6 of 11

- 22. (Original) The MMI of Claim 14 wherein the thumb-operable input device comprises at least one of a fingerprint sensor, touchpad or hinged bar, wherein the indicator is configured to move between menu items responsive to upward and/or downward movement on the fingerprint sensor, the touchpad or the hinged bar.
- 23. (Original) The MMI of Claim 14 wherein the thumb-operable input device comprises a touchpad.
- 24. (Original) The MMI of Claim 23 wherein the touchpad is operatively associated with a sensor that is configured to detect movement on the touchpad and wherein the sensor is operatively associated with a processor that is configured to process the detected movement on the touchpad and move the indicator on the display between the menu items responsive to the processed movement.
- 25. (Original) A method of operating a portable electronic device comprising positioning an indicator on a display to highlight and/or select menu items on the display responsive to input received at a thumb-operable input device.
- 26. (Original) The method of Claim 25, further comprising:
 detecting movement on the thumb-operable input device;
 processing the detected movement; and
 moving the indicator on the display between the menu items responsive to the
 processed movement.
- 27. (Original) The method of Claim 26 wherein detecting movement on the thumb-operable input device comprises detecting movement via fingerprint analysis.
- 28. (Original) The method of Claim 27, wherein detecting movement further comprises:

detecting distortion of a fingerprint on the thumb-operable input device; and processing the detected distortion of the fingerprint; and highlighting and/or selecting menu items on the display responsive to the

Serial No.: 10/783,601 Filed: February 20, 2004

Page 7 of 11

processed distortion.

29. (Original) The method of Claim 25 wherein positioning the indicator comprises sliding a bar in a slot in a housing of the portable electronic device to position the indicator on the display to highlight and/or select one of a plurality of menu items.

30. (Original) The method of Claim 29 wherein positioning the indicator further comprises:

moving the bar in the slot between a plurality of notches associated with one of the plurality of menu items to position the indicator on the display to highlight and/or select the associated menu item.

- 31. (Original) The method of Claim 29 further comprising repositioning the bar at an end of the slot between selections of menu items.
- 32. (Original) The method of Claim 25 wherein positioning the indicator further comprises moving the indicator between the menu items responsive to upward and/or downward movement on a fingerprint sensor, a touchpad or a hinged bar.